



FURBISH CHEMICAL & SUPPLY CO. Of ALASKA, INC.

501 Raspberry Road

Anchorage, Alaska 99518-1569

Phone (907) 344-4184 Fax (907) 344-5919

CLEAR SHYNE

Floor Finish

DESCRIPTION: This product is the latest formulation in metal cross link Acrylic Polymer Floor Finishes. It has a film, a non buff hardener, yet responds to Spray Buffing and Hi Speed Buffing. It dries to a colorless slip resistant film in less than 15 minutes in average temperature and humidity conditions. It dries to a bright gloss and regular maintenance with a Hi Speed floor machine will result in a mirror like gloss.

ADVANTAGES:

- Easy to apply--Ease of maintenance.
- Long wearing--Tough--Greater wearability.
- Extremely high gloss, without buffing.
- Improved black mark resistance.
- Outstanding slip resistance.
- High response to spray buff maintenance, particularly high speed systems.
- Easy cleaning, re-coating & longer life, reduces material cost & labor.
- Exceptional resistance to powdering.
- Excellent re-coat properties.
- Scuffing reduced to a minimum.
- Colorless film, no discoloration...even on white floors.
- Better re-movability than conventional finishes.
- Seals floor as it finishes.
- Fast drying.
- Gloss--easily renewed upon buffing.

You can tell that this floor finish is one of the best floor finishes on the market when you put it down on those heavily trafficked areas. It remains bright and shiny without scuffs or black marks while leading itself to spray buffing to quickly repair any worn places.

Floors in shopping centers, malls, hospitals, auditoriums, stores, offices and other heavy pedestrian traffic areas really take a beating. This is an outstanding cross linked Acrylic Polymer Scrubbable floor finish with an excellent durability. The special acrylic polymers make it highly resistant to alkaline builders and cleaners. It dries to a bright, scuff and scratch resistant coat in 15 minutes and has a remarkably hard finish.

This product is recommended for use on many surfaces--vinyl asbestos, vinyl, asphalt, ceramic tile, concrete, linoleum, marble, terrazzo, rubber, sealed or painted wood. It's self polishing, anti-slip, water and detergent resistant, yet completely removable with ammoniated strippers. It out lasts and out shines any other floor finish. Bring the luster back to your floors with this hard working product. It's fast and easy.

NOTICE:

The information contained herein, is to the best of our knowledge and belief, accurate. Since the conditions of handling and use are beyond our control, we make no guarantee of results. We assume no liability for damages or penalties resulting from our suggestions or recommendations, nor are these to be taken as a license to operate under, or recommendations to infringe, any patent.

APPLICATION: Completely strip old coating from floor. Thoroughly rinse all dirt and stripper

solution from floor. For best results, use neutralizer rinse additive in you first rinse. Complete stripping and rinsing includes removal of build up along edges and in corners. Apply a full uniform coat after floor is thoroughly dry. A second coat is recommended on newly stripped floors. Extremely porous floors can require three or four coats. For mirror like gloss apply minimum 3 coats of finish. Dry buff with white pad only on Hi Speed Machine.

CARE: Floors should be dust mopped daily to remove abrasive soil. Food areas should be damp mopped regularly with a diluted detergent solution. Clean floor with a mild detergent solution and rinse when recoating is needed. Remove all dirt and dust when spray buffing the floor. Follow recommended procedures for spray buffing. Use a dust mop afterwards to remove any dust generated from spray buffing. If needed, apply a thin coat of the floor finish.

SPECIFICATIONS:

Detergent resistance.....	Excellent
Color.....	Milky White
Film color.....	Clear not harmed by sunlight Non Yellowing
Odor.....	Extremely pleasant, polymer odor
Percent Solids.....	18.0±0.5%
Flash Point.....	None
pH.....	9.0±0.2
Drying Time.....	15 minutes
Re-capability.....	Excellent
Leveling all Types of Floors.....	Excellent
Stability.....	Excellent
Water Resistance.....	Excellent
Initial Gloss.....	Excellent
Specific Gravity.....	1.033±0.005
Slip Resistance.....	0.60 (James Method)
Slip Resistance (Foot Pressure).....	Excellent
Scuff Resistance.....	Excellent
Heel Mark Resistance.....	Excellent
Abrasion Resistance.....	Excellent
Film Healing.....	Recovers when buffed
Film Powdering.....	None
Durability.....	Excellent
Coverage.....	2,000 sq. ft/gallon

CAUTION

**KEEP OUT OF REACH OF CHILDREN
DO NOT TAKE INTERNALLY
PROTECT FROM FREEZING**